

STANDARD EnviroQuiet®

US PATENTS 8640824 & 8893850



Standard EnviroQuiet is composed of 2mm thick LVT permanently affixed to a 3mm thick recycled rubber underlayment, yielding an overall thickness of 5mm. The 8mil clear wear layer provides longlasting durability in residential areas, making it a great choice for multi-family and student housing. Upgrade to a 12mil wear layer for increased durability.

ENVIROQUIET ON DEMAND

A preferred selection of our most popular styles, for which we maintain higher volumes of stock, so it's readily available when you need it.

SALES@FLOORFOLIO.COM | 800-671-1124

ONE COST. ONE INSTALLATION. ONE SOLUTION.

EnviroQuiet luxury vinyl flooring is manufactured with the sound reducing underlayment attached, so it can be purchased and installed as one fully integrated product. The double patented formula provides an all-in-one, economical flooring solution that can be paired with any of our stunning wood or stone visuals.

ASTM F 1700	Vinyl Tile Portion	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Class 1
ASTM E 648	Fire Resistance	Pass
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 *modified	Static Load	500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	0.008" / 0.012"
ASTM F 386	Overall Thickness	5mm (0.197")