



ONE COST. ONE INSTALLATION. ONE SOLUTION

EnviroQuiet luxury vinyl flooring is manufactured with the sound reducing rubber underlayment attached, so it can be purchased and installed as one fully integrated product. With 5 patents worldwide, this formula provides an all-in-one economical flooring solution that can be paired with most of our wood or stone visuals.

ASTM F 1700	Vinyl Tile Portion	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 *modified	Static Load	500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	8 mil or 12 mil
ASTM F 386	Overall Thickness	5mm

EnviroQuiet 5.0 is composed of 2mm thick LVT permanently affixed to a 3mm thick acoustical rubber underlayment, yielding an overall thickness of 5mm. The 8mil clear wear layer provides long lasting durability in residential areas, making it a great choice for multi-family and student housing. Upgrade to a 12mil wear layer for increased durability.



US PATENTS

8,640,824
 8,893,850
 10,604,946B2

CAN PATENT

2,899,742

EU PATENT

2662508B

EnviroQuiet 5.0 Technical Specifications
 sales@floorfolio.com | (800) 671-1124
 floorfolio.com

Rev. 11/20