

ONE COST. ONE INSTALLATION. ONE SOLUTION

EnviroQuiet luxury vinyl flooring is manufactured with the sound reducing rubber underlayment attached, so it can be purchased and installed as one fully integrated product. With 5 patents worldwide, this formula provides an all-in-one economical flooring solution that can be paired with most of our stunning wood or stone visuals.

ASTM F 1700	Vinyl Tile Portion	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 *modified	Static Load	500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	22 mil
ASTM F 386	Overall Thickness	6mm

With an overall thickness of 6mm, each plank is composed of 3mm thick LVT permanently affixed to 3mm thick, extra dense rubber underlayment. The 22 mil clear wear layer on 3mm LVT is a durable, low maintenance solution for high traffic, commercial areas such as hospitals, hotels, restaurants and retail locations.

FLOORFOLIO®

US PATENTS

8,640,824
8,893,850
10,604,946 B2

CAN PATENT

2,899,742

EU PATENT

2662508B

EnviroQuiet 6.0 Technical Specifications

sales@floorfolio.com | (800) 671-1124

floorfolio.com

Rev. 11/20