



**ONE COST. ONE INSTALLATION. ONE SOLUTION**

EnviroQuiet 5.0 is 2mm LVT factory laminated to a 3mm thick acoustical underlayment, so it can be purchased and installed as one fully integrated product. With 5 patents worldwide, this formula provides an all-in-one economical flooring solution that can be paired with most of our wood or stone visuals.

ASTM F 1700	Vinyl Tile Portion	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 *modified	Static Load	500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	8 mil or 12 mil
ASTM F 386	Overall Thickness	5mm

EnviroQuiet 5.0 yields an overall thickness of 5mm. The 8mil clear wear layer provides long lasting durability in residential areas, making it a great choice for multi-family and student housing. Upgrade to a 12mil wear layer for increased durability.



**US PATENTS**

8,640,824  
 8,893,850  
 10,604,946B2

**CAN PATENT**

2,899,742

**EU PATENT**

2662508B

EnviroQuiet 5.0 Technical Specifications  
 sales@floorfolio.com | (800) 671-1124  
 floorfolio.com

Rev. 6/23