

ONE COST. ONE INSTALLATION. ONE SOLUTION

EnviroQuiet 6.0 is commercial grade 3mm LVT factory laminated to a 3mm thick acoustical underlayment, so it can be purchased and installed as one fully integrated product. With 5 patents worldwide, this formula provides an all-in-one economical flooring solution that can be paired with most of our stunning wood or stone visuals

ASTM F 1700	Vinyl Tile Portion	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 *modified	Static Load	500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	22 mil
ASTM F 386	Overall Thickness	6mm

With an overall thickness of 6mm, the 22 mil clear wear layer on 3mm LVT is a durable, low maintenance solution for high traffic, commercial areas such as hospitals, hotels, restaurants and retail locations.

FLOORFOLIO®

US PATENTS

8,640,824
8,893,850
10,604,946 B2

CAN PATENT

2,899,742

EU PATENT

2662508B

EnviroQuiet 6.0 Technical Specifications

sales@floorfolio.com | (800) 671-1124
floorfolio.com

Rev. 6/23