



floorfolio®

# 2mm CHEVRON COLLECTION



725-1621-1-B + 725-1621-2-B (8 mil)  
725-1621-1-A + 725-1621-2-A (12 mil)



725-1622-1-B + 725-1622-2-B (8 mil)  
725-1622-1-A + 725-1622-2-A (12 mil)



725-1623-1-B + 725-1623-2-B (8 mil)  
725-1623-1-A + 725-1623-2-A (12 mil)



725-1627-1-B + 725-1627-2-B (8 mil)  
725-1627-1-A + 725-1627-2-A (12 mil)



725-1628-1-B + 725-1628-2-B (8 mil)  
725-1628-1-A + 725-1628-2-A (12 mil)

## STANDARD PLANK

- 7.25" x 48" Plank
- 2mm Gauge
- 8 mil or 12 mil Wear Layer
- Embossed Texture
- Urethane Finish



PLANK 1



PLANK 2

Plank 1 and Plank 2 seamlessly form the "V" shape when the planks are installed next to each other.

## Technical Specifications

|                        |                         |                              |
|------------------------|-------------------------|------------------------------|
| ASTM F 1700            | Solid Vinyl Tile        | Class III, Type A or B, Pass |
| ASTM E 662             | Smoke Density           | Pass                         |
| ASTM E 648             | Fire Resistance         | Class 1                      |
| ASTM D 204             | Coefficient of Friction | Pass                         |
| ASTM F 970             | Static Load             | 250 PSI                      |
| ASTM F 970 (*modified) | Static Load             | 2,500 PSI                    |
| ASTM F 925             | Chemical Resistance     | Pass                         |
| ASTM F 410             | Wear Layer Thickness    | 8 mil or 12 mil              |
| ASTM F 386             | Overall Thickness       | 2mm                          |

• The Chevron Collection is also available in: 3mm with 20 mil wear layer.



floorfolio®

floorfolio.com • sales@floorfolio.com • (800) 671-1124  
2mm Chevron Collection © Mar 2023