



floorfolio®

# 2mm COASTLINE COLLECTION



748-6821-B-51 (8 mil)  
748-6821-A-51 (12 mil)



748-6822-B-51 (8 mil)  
748-6822-A-51 (12 mil)



748-6828-B-51 (8 mil)  
748-6828-A-51 (12 mil)

### SPECIAL ORDER

- 7" x 48" Plank
- 2mm Gauge
- 8 mil or 12 mil Wear Layer
- Smooth Texture
- Urethane Finish

### Technical Specifications

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 (*modified)	Static Load	2,500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	8 mil or 12 mil
ASTM F 386	Overall Thickness	2mm

• The Coastline Collection comes standard in: 3mm with a 22 mil wear layer  
 • Special Order (minimums apply): 2mm with an 8 or 12 mil wear layer | EnviroQuiet



floorfolio®