

floorfolio[™] 2mm MAPLEWOOD COLLECTION




* HS

748-108-B-51 (8 mil)
748-108-A-51 (12 mil)



* SM

748-460-B-51 (8 mil)
748-460-A-51 (12 mil)



* SM

748-462-B-51 (8 mil)
748-462-A-51 (12 mil)




* SM

748-463-B-51 (8 mil)
748-463-A-51 (12 mil)



* SM

748-464-B-51 (8 mil)
748-464-A-51 (12 mil)




* SM

748-465-B-51 (8 mil)
748-465-A-51 (12 mil)




* SM

748-466-B-51 (8 mil)
748-466-A-51 (12 mil)




* SM

748-467-B-51 (8 mil)
748-467-A-51 (12 mil)



* SM

748-468-B-51 (8 mil)
748-468-A-51 (12 mil)



* SM

748-469-B-51 (8 mil)
748-469-A-51 (12 mil)

STANDARD PLANK

- 7" x 48" Plank
- 2mm Gauge
- 8 mil or 12 mil Wear Layer
- HS – Hand-Scraped | ▪ SM - Smooth
- Urethane Finish



Technical Specifications

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 (*modified)	Static Load	2,500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	8 mil or 12 mil
ASTM F 386	Overall Thickness	2mm

- The Maplewood Collection is available in standard: 3mm with a 22 mil wear layer
- Special Order (minimums apply): 2mm with an 8 or 12 mil wear layer | EnviroQuiet

floorfolio[®]

floorfolio.com • sales@floorfolio.com • (800) 671-1124
2mm Maplewood Collection © May 2023