



floorfolio®

3mm MAPLEWOOD COLLECTION



* HS

725-108 (22 mil)



* SM

725-460 (22 mil)



* SM

725-462 (22 mil)




* SM

725-463 (22 mil)



* SM

725-464 (22 mil)




* SM

725-465 (22 mil)




* SM

725-466 (22 mil)




* SM

725-467 (22 mil)



* SM

725-468 (22 mil)



* SM

725-469 (22 mil)

STANDARD PLANK

- 7.25" x 48" Plank
- 3mm Gauge
- 22 mil Wear Layer
- HS – Hand-Scraped | ▪ SM - Smooth
- Urethane Finish



Technical Specifications

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 (*modified)	Static Load	2,500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	22 mil
ASTM F 386	Overall Thickness	3mm

- The Maplewood Collection comes standard in: 3mm with a 22 mil wear layer
- Special Order (minimums apply): 2mm with an 8 or 12 mil wear layer | EnviroQuiet

floorfolio®

floorfolio.com • sales@floorfolio.com • (800) 671-1124
3mm Maplewood Collection © May 2023