



floorfolio®

# 2mm OMBRE COLLECTION



648-701-B (8 mil)  
648-701-A (12 mil)




648-702-B (8 mil)  
648-702-A (12 mil)



648-703-B (8 mil)  
648-703-A (12 mil)



648-704-B (8 mil)  
648-704-A (12 mil)



648-705-B (8 mil)  
648-705-A (12 mil)



648-706-B (8 mil)  
648-706-A (12 mil)



648-707-B (8 mil)  
648-707-A (12 mil)



648-708-B (8 mil)  
648-708-A (12 mil)



648-710-B (8 mil)  
648-710-A (12 mil)



648-711-B (8 mil)  
648-711-A (12 mil)

## STANDARD PLANK

- 6" x 48" Plank
- 2mm Gauge
- 8 mil or 12 mil Wear Layer
- Wood Grain
- Urethane Finish

## Technical Specifications

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 (*modified)	Static Load	2,500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	8 mil or 12 mil
ASTM F 386	Overall Thickness	2mm

- The Ombre Collection comes standard in: 3mm with a 22 mil wear layer
- Special Order (minimums apply): 2mm with an 8 or 12 mil wear layer | EnviroQuiet



floorfolio®

floorfolio.com • sales@floorfolio.com • (800) 671-1124  
2mm Ombre Collection © May 2023