



floorfolio® 3mm OMBRE COLLECTION



648-701 (22 mil)



648-702 (22 mil)



648-703 (22 mil)



648-704 (22 mil)



648-705 (22 mil)



648-706 (22 mil)



648-707 (22 mil)



648-708 (22 mil)



648-710 (22 mil)



648-711 (22 mil)

STANDARD PLANK

- 6" x 48" Plank
- 3mm Gauge
- 22 mil Wear Layer
- Wood Grain
- Urethane Finish

Technical Specifications

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 (*modified)	Static Load	2,500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	22 mil
ASTM F 386	Overall Thickness	3mm

- The Ombre Collection comes standard in: 3mm with a 22 mil wear layer
- Special Order (minimums apply): 2mm with an 8 or 12 mil wear layer | EnviroQuiet



floorfolio®

floorfolio.com • sales@floorfolio.com • (800) 671-1124
3mm Ombre Collection © May 2023