



floorfolio® 2mm TIMBER COLLECTION

* WG



636-604-B-H (8 mil)
636-604-A-H (12 mil)

* HS



636-670-B-H (8 mil)
636-670-A-H (12 mil)

* HS



636-671-B-H (8 mil)
636-671-A-H (12 mil)

* HS



636-672-B-H (8 mil)
636-672-A-H (12 mil)

* HS



636-673-B-H (8 mil)
636-673-A-H (12 mil)

* HS



636-674-B-H (8 mil)
636-674-A-H (12 mil)

* HS



636-676-B-H (8 mil)
636-676-A-H (12 mil)

* HS



636-677-B-H (8 mil)
636-677-A-H (12 mil)

* HS



636-679-B-H (8 mil)
636-679-A-H (12 mil)

STANDARD PLANK

- 6" x 36" Plank
- 2mm Gauge
- 8 mil or 12 mil Wear Layer
- HS – Hand-Scraped | ▪ WG – Wood Grain
- Urethane Finish

Technical Specifications

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 (*modified)	Static Load	2,500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	8 mil or 12 mil
ASTM F 386	Overall Thickness	2mm

- The Timber Collection comes standard in: 3mm with a 22 mil wear layer
- Special Order (minimums apply): 2mm with an 8 or 12 mil wear layer | EnviroQuiet



floorfolio®

floorfolio.com • sales@floorfolio.com • (800) 671-1124
2mm Timber Collection © May 2023