



floorfolio®

3mm TIMBER COLLECTION



* WG

636-604 (22 mil)



* HS

636-670-H (22 mil)



* HS

636-671-H (22 mil)



* HS

636-672-H (22 mil)



* HS

636-673-H (22 mil)



* HS

636-674-H (22 mil)



* HS

636-676-H (22 mil)



* HS

636-677-H (22 mil)



* HS

636-679-H (22 mil)

STANDARD PLANK

- 6" x 36" Plank
- 3mm Gauge
- 22 mil Wear Layer
- HS – Hand-Scraped | ▪ WG – Wood Grain
- Urethane Finish

Technical Specifications

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Pass
ASTM E 648	Fire Resistance	Class 1
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 (*modified)	Static Load	2,500 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	22 mil
ASTM F 386	Overall Thickness	3mm



floorfolio®

floorfolio.com • sales@floorfolio.com • (800) 671-1124
3mm Timber Collection © May 2023

• The Timber Collection comes standard in: 3mm with a 22 mil wear layer
• Special Order (minimums apply): 2mm with an 8 or 12 mil wear layer | EnviroQuiet