

# FLOORFOLIO 9200 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 09/30/2024

Version: 2.3

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** FLOORFOLIO 9200 A

### Intended Use of the Product

**Use of the Substance/Mixture:** No use is specified.

### Name, Address, and Telephone of the Responsible Party

#### **Company**

FloorFolio Industries  
110 Mayfield Avenue  
Edison, N.J. 08837  
732-287-8200

#### **Manufacturer**

Helmitin Inc.  
11110 Airport Road  
Olive Branch, MS 38654  
Phone: 877.823.2624  
www.helmitin.com

### Emergency Telephone Number

**Emergency Number** : CHEMTREC 1-800-424-9300

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Repr. 2 H361

Full text of H-phrases: see section 16

### Label Elements

#### **GHS-US Labeling**

##### **Hazard Pictograms (GHS-US)**

:



GHS07



GHS08

##### **Signal Word (GHS-US)**

: Danger

##### **Hazard Statements (GHS-US)**

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H361 - Suspected of damaging fertility or the unborn child (oral).

##### **Precautionary Statements (GHS-US)**

: P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

### Unknown Acute Toxicity (GHS-US) Not available

# FLOORFOLIO 9200 A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

| Name  | Product Identifier   | % (w/w)   |
|---|----------------------|-----------|
| Bisphenol A-epichlorohydrin polymer   | (CAS No) 25068-38-6  | 10 - 30   |
| Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (Polyurethane Prepolymer) | (CAS No) 102900-03-8 | 10 - 30   |
| Alkyl (C12-14) glycidyl ether   | (CAS No) 68609-97-2  | 5 - 10    |
| Trimethylolpropane triacrylate  | (CAS No) 15625-89-5  | 1 - 5     |
| Phenol, 4-nonyl-, branched  | (CAS No) 84852-15-3  | 0.5 – 1.5 |
| Quartz*   | (CAS No) 14808-60-7  | 0.1 – 1.0 |

\*This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Irritation to eyes, skin and respiratory tract. May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child (oral).

**Inhalation:** May cause respiratory irritation.

**Skin Contact:** Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Eye Contact:** Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, and burning, tearing, and blurred vision.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child (oral).

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

### SECTION 5: FIRE-FIGHTING MEASURES

#### Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, dry chemical, or sand.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Potentially violent decomposition can occur above 350 °C.

**Explosion Hazard:** Product is not explosive but if hazardous polymerization occurs can have an oxidizing effect that could lead to fire and possible explosion.

**Reactivity:** Hazardous polymerization can occur in contact with certain incompatible materials.

#### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

# FLOORFOLIO 9200 A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Under fire conditions this material may produce hazardous carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Use only outdoors or in a well-ventilated area.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Use only non-sparking tools.

### Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Additional Hazards When Processed:** The substance will polymerize due to heating, on contact with incompatible materials, and under the influence of light. Heating may cause violent combustion or explosion producing acrid smoke. The substance may also spontaneously polymerize if it is not stabilized. Product to be handled in a closed system and under strictly controlled conditions.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

**Storage Conditions:** Store in a dry, cool, and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Amines. Fluorine. Ammonium salts.

### Specific End Use(s)

No use is specified.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

| Quartz (14808-60-7) |                                |   |
|---------------------|--------------------------------|---|
| USA ACGIH           | ACGIH TWA (mg/m <sup>3</sup> ) | 0.025 mg/m <sup>3</sup> (respirable fraction) |
| USA ACGIH           | ACGIH chemical category        | A2 - Suspected Human Carcinogen               |

# FLOORFOLIO 9200 A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                         |                                      |   |
|-------------------------|--------------------------------------|---|
| USA OSHA                | OSHA PEL (STEL) (mg/m <sup>3</sup> ) | 250 mppcf/%SiO <sub>2</sub> +5, 10mg/m <sup>3</sup> /%SiO <sub>2</sub> +2 |
| USA NIOSH               | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 0.05 mg/m <sup>3</sup> (respirable dust)                                  |
| USA IDLH                | US IDLH (mg/m <sup>3</sup> )         | 50 mg/m <sup>3</sup> (respirable dust)                                    |
| Alberta                 | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable particulate)                          |
| British Columbia        | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable)                                      |
| Manitoba                | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable fraction)                             |
| New Brunswick           | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup> (respirable fraction)                               |
| Newfoundland & Labrador | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable fraction)                             |
| Nova Scotia             | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable fraction)                             |
| Nunavut                 | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup> (respirable mass)                                   |
| Northwest Territories   | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup> (respirable mass)                                   |
| Ontario                 | OEL TWA (mg/m <sup>3</sup> )         | 0.10 mg/m <sup>3</sup> (designated substances regulation-respirable)      |
| Prince Edward Island    | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable fraction)                             |
| Québec                  | VEMP (mg/m <sup>3</sup> )            | 0.1 mg/m <sup>3</sup> (respirable dust)                                   |
| Saskatchewan            | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup> (respirable fraction)                              |
| Yukon                   | OEL TWA (mg/m <sup>3</sup> )         | 300 particle/mL   |

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

**Personal Protective Equipment:** Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

**Consumer Exposure Controls:** Do not eat, drink or smoke during use

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

|                           |                                       |
|---------------------------|---------------------------------------|
| Physical State            | : Paste – Viscous Liquid              |
| Appearance                | : Beige Thick liquid                  |
| Odor                      | : Not available                       |
| Odor Threshold            | : Not available                       |
| pH                        | : Not available                       |
| Evaporation Rate          | : Not available                       |
| Melting Point             | : Not available                       |
| Freezing Point            | : 32° F                               |
| Boiling Point             | : > 425 °F (218 °C)                   |
| Flash Point               | : > 200 °F (93 °C) (Setaflash method) |
| Auto-ignition Temperature | : Not available                       |
| Decomposition Temperature | : Not available                       |
| Flammability (solid, gas) | : Not available                       |
| Lower Flammable Limit     | : Not available                       |
| Upper Flammable Limit     | : Not available                       |

# FLOORFOLIO 9200 A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|   |   |
|---|---|
| Vapor Pressure                                    | : Not available   |
| Relative Vapor Density at 20 °C                   | : Not available   |
| Relative Density                                  | : Not available   |
| Specific Gravity                                  | : 1.5   |
| Solubility  | : Not available   |
| Partition Coefficient: N-Octanol/Water            | : Not available   |
| Viscosity   | : Approximately 85,000 cps  |
| Explosion Data – Sensitivity to Mechanical Impact | : Not expected to present an explosion hazard due to mechanical impact. |
| Explosion Data – Sensitivity to Static Discharge  | : Not expected to present an explosion hazard due to static discharge.  |
| VOC Content (SCAQMD Rule 1168)                    | : <12 g/L (<0.1 lbs/gal)  |

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions are unlikely to occur under normal circumstances.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization can occur in contact with certain incompatible materials.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Amines. Fluorine. Ammonium salts.

**Hazardous Decomposition Products:** Under fire conditions this material may produce hazardous carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not classified

**Carcinogenicity:** Not classified.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child (oral).

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child (oral).

### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

| Bisphenol A-epichlorohydrin polymer (25068-38-6) |              |
|--|--------------|
| LD50 Oral Rat                                    | > 2000 mg/kg |
| LD50 Dermal Rat                                  | > 2000 mg/kg |
| Phenol, 4-nonyl-, branched (84852-15-3)          |              |
| LD50 Oral Rat                                    | 580 mg/kg    |
| LD50 Dermal Rabbit                               | 2031 mg/kg   |
| Phenol (108-95-2)                                |              |
| LD50 Oral Rat                                    | 340 mg/kg    |

# FLOORFOLIO 9200 A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|  |  |
|--|--|
| LD50 Dermal Rabbit                                 | 630 mg/kg                                |
| LC50 Inhalation Rat                                | 0.316 mg/l/4h (reported as 316 mg/m3/4h) |
| ATE US (gases)                                     | 700.00 ppmV/4h                           |
| <b>Quartz (14808-60-7)</b>                         |  |
| LD50 Oral Rat                                      | > 5000 mg/kg                             |
| LD50 Dermal Rat                                    | > 5000 mg/kg                             |
| <b>Trimethylolpropane triacrylate (15625-89-5)</b> |  |
| LD50 Dermal Rabbit                                 | 5000 mg/kg                               |
| <b>Quartz (14808-60-7)</b>                         |  |
| IARC Group   | 1  |
| National Toxicology Program (NTP) Status           | Known Human Carcinogens.                 |
| <b>Trimethylolpropane triacrylate (15625-89-5)</b> |  |
| National Toxicology Program (NTP) Status           | Evidence of Carcinogenicity.             |

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

Ecology - General: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

|   |   |
|---|---|
| <b>Bisphenol A-epichlorohydrin polymer (25068-38-6)</b> |   |
| LOEC (acute)  | 1 mg/l Daphnia magna  |
| NOEC chronic crustacea                                  | 0.3 mg/l Daphnia magna  |
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b>          |   |
| LC50 Fish 1   | 0.135 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])  |
| EC50 Daphnia 1  | 0.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)                        |
| LC 50 Fish 2  | 0.1351 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through]) |

### Persistence and Degradability

### Bioaccumulative Potential

|  |     |
|--|-----|
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b> |     |
| BCF Fish 1                                     | 271 |

**Mobility in Soil** Not available

### Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Sewage Disposal Recommendations:** This material is hazardous to the aquatic environment. Keep out of sewers and waterways. Do not empty into drains; dispose of this material and its container in a safe way.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

**In Accordance with DOT** Not regulated for transport

**In Accordance with IMDG** Not regulated for transport

**In Accordance with IATA** Not regulated for transport

**In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

|   |  |
|---|--|
| SARA Section 311/312 Hazard Classes                                       | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
| <b>Bisphenol A-epichlorohydrin polymer (25068-38-6)</b>                   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |

# FLOORFOLIO 9200 A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|  |  |
|--|--|
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Listed on United States SARA Section 313  |  |
| <b>EPA TSCA Regulatory Flag</b>  | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.<br>S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule. |
| <b>SARA Section 313 - Emission Reporting</b>   | 1.0 %  |
| <b>Alkyl (C12-14) glycidyl ether (68609-97-2)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>EPA TSCA Regulatory Flag</b>  | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.   |
| <b>Propanol, oxybis-, dibenzoate (27138-31-4)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>Quartz (14808-60-7)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (102900-03-8) (Polyurethane Prepolymer)</b> |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>Trimethylolpropane triacrylate (15625-89-5)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |

### US State Regulations

**Proposition 65** –  **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

|   |
|---|
| <b>Quartz (14808-60-7)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |

### Canadian Regulations

|  |
|--|
| <b>Bisphenol A-epichlorohydrin polymer (25068-38-6)</b>  |
| Listed on the Canadian DSL (Domestic Substances List)  |
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b>   |
| Listed on the Canadian DSL (Domestic Substances List)  |
| <b>Alkyl (C12-14) glycidyl ether (68609-97-2)</b>  |
| Listed on the Canadian DSL (Domestic Substances List)  |
| <b>Propanol, oxybis-, dibenzoate (27138-31-4)</b>  |
| Listed on the Canadian DSL (Domestic Substances List)  |
| <b>Quartz (14808-60-7)</b>   |
| Listed on the Canadian DSL (Domestic Substances List)<br>Listed on the Canadian IDL (Ingredient Disclosure List)<br>IDL Concentration 1 %  |
| <b>Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (102900-03-8) (Polyurethane Prepolymer)</b> |
| Listed on the Canadian DSL (Domestic Substances List)  |
| <b>Trimethylolpropane triacrylate (15625-89-5)</b>   |
| Listed on the Canadian DSL (Domestic Substances List)  |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

# FLOORFOLIO 9200 A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 09/30/2024

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**GHS Full Text Phrases:**

|      |   |
|------|---|
| H315 | Causes skin irritation                              |
| H317 | May cause an allergic skin reaction                 |
| H319 | Causes serious eye irritation                       |
| H361 | Suspected of damaging fertility or the unborn child |
| H402 | Harmful to aquatic life                             |

North America GHS US 2012 & WHMIS 2015